



PIEMME ELEKTRA SRL
TRASFORMATORI

Piemme Elektra s.r.l. Unipersonale
Viale Italia, 8 65010 Collecervino (PE) Italy
Tel. +39 (0)85 82 93 091 – info@piemme-elektra.it
www.piemme-elektra.it VAT IT 01812670683

Updates:

Rev.	Modifications	Date	Approval
00	DRAFT	02/02/24	Maurizio Parlione

SPECIFICATION / DATA SHEET					
	Order Code	Rev.	Date	Description	Page
	LT20024	01	02/02/24	Common Mode – Power line Choke	1 di 3

Electrical Properties:

Properties		Test Conditions	Value	Unit	Tol.
Number of windings	N	-	2	-	-
Rated Current	Ir	@ 70°C	3	A	Max
Working frequency	F	-	400	Hz	+/-20%
Inductance	L	1kHz 1V	33	mH	+/-40%
DC Resistance	Rdc	@ 20°C	80	mOhm	Max
Power Loss	WI	@ 70°C – 3A	2	W	Max
Self Resonant Frequency	SRF	-	320	kHz	+/-20kHz
Impedance	Z	150kHz	20	kOhm	Typ.
Common Mode Typical Attenuation	Att.	@150kHz 50 Ohm	48	dB	Typ.
Insulation Test Voltage	Vt	50Hz/1mA/10 sec	1500	Vac	-
Insulation resistance	Ir	500VDC	10	MOhm	Min

Certification/Compliance:

RoHS 	Compliant (2011/65/EU & 2015/863)
REACH 	Conform or declared (EC 1907/2006)
Flammability	UL94-V0 Compliant
MIL-PFR-27 – Transformer and Inductor – General Specification For	Compliant
MIL-STD-202 – Test Method Standard – Electronic end Electrical Component Parts	
IPC-A-610D – Acceptability of Electronic Assemblies	


General Properties:

Ambient Temperature (referring to Ir)	-40 up to +85°C
Operating Temperature	-40 up to +125°C
Temperature Rise	Max 70°C
Storage Conditions (in original packaging)	< 40°C - <75% RH
Weight	33gr


All values and tolerance refer to room temperature if not specified differently

SPECIFICATION / DATA SHEET

	Order Code	Rev.	Date	Description	Page
	LT20024	01	02/02/24	Common Mode – Power line Choke	2 di 3


Dimensions (mm):

BOTTOM VIEW




Dimensions in millimeters

General Tolerance DIN ISO 2768-C

Schematic:**Marking:**

Logo
PME - Data Code
LT20024 Revxx

Recommended Hole Pattern (mm):

TOP VIEW

Dimensions in millimeters

SPECIFICATION / DATA SHEET

	Order Code	Rev.	Date	Description	Page
	LT20024	01	02/02/24	Common Mode – Power line Choke	3 di 3